

	Max. bel./ isol. (kg)	A (mm)	B (mm)	H (mm)	D	Vikt (kg)
32 LV 10/120	120	76	61	42	M10	0,4
32 LV 10/200	200	92	79	42	M10	0,6
32 LV 10/300	300	108	92	42	M12	0,8
32 LV 10/600	600	144	124	42	M12	1,3
32 LV 16/200	200	170		72	M12	3,1
32 LV 16/300	300	170		72	M12	3,1
32 LV 16/400	400	170		72	M12	3,2
32 LV 16/700	700	170		72	M12	3,4
32 LV 16/1000	1 000	220		76	M16	6,8
32 LV 16/1500	1 500	220		76	M16	7,2
32 LV 24/200	200	170		104	M12	4,0
32 LV 24/300	300	170		104	M12	4,1
32 LV 24/400	400	170		104	M12	4,2
32 LV 24/700	700	170		104	M12	4,5
32 LV 24/1000	1 000	220		109	M16	8,9
32 LV 24/1500	1 500	220		109	M16	9,5
32 LV 40/200	200	220		165	M16	11,5
32 LV 40/300	300	220		165	M16	11,7
32 LV 40/400	400	220		165	M16	11,9
32 LV 40/700	700	220		165	M16	12,5
32 LV 40/1000	1 000	220		165	M16	13,2
32 LV 40/1500	1 500	220		165	M16	14,2



Isolator 32 LV har även gänga på undersidan.